

HV

Contact

Jutta Geurtz
+49 2336 808 364
jgeurtz@titan-schwelm.de



Sealer for steel strap

Convenient and versatile

The HV sealer from TITAN is designed for the purely manual seal joint with one notch. The tool is characterised by its low weight of just 3 kg, a feature that ensures high demand especially in mobile applications.

The minimalist design and robust technology make this sealer a particularly inexpensive and popular solution. Common applications include steel service centres.

Circular and flat packages even with comparably small dimensions are no problem for the HV. You can use the tool to join the seal types RSK/RSL 19, RSK/RSL 25 and RSK/RSL 32.

The matching counterpart of this sealer is the manual tensioner HR32. Combined, they perform complete strapping..

Technical Data

Kind of drive (sealing)	Manually
Dimensions	approx. 700 x 160 x 50 mm (L x W x H) HV/19 approx. 700 x 175 x 50 mm (L x W x H) HV/32 approx. 27.56 x 6.29 x 1.97" (L x W x H) HV/19 approx. 27.56 x 6.89 x 1.97" (L x W x H) HV/32
Weight	6.28 lb

Strap/Joint

Type of strap	Steel strap
Strap	Automatenband
Strap width	19, 25, 32 mm 3/4" ; 1" ; 1 1/4"
Strap thickness	0.80 - 1.00 mm 0.031 - 0.039 in
Kind of seal	Seal-joint (single notch)