

TA260



Contact

Anke Freitag
+49 2336 808 295
afreitag@titan-schwelm.de



Battery powered tool for plastic strap

TA260 - The digital professional

The new TA 260 is a innovative and revolutionary battery strapping tool, developed for 13 – 16 mm PP and PET strap.

Lightweight, well balanced, ergonomic and easy to use.

The TA 260 can work in three different operating modes (fully automatic, semi-automatic and manual).

Developed without the standard opening lever for a more comfortable strapping operation. With the integrated Bluetooth connection you can set, check and update your tool. You can also use your mobile devices (APP available for Android and iOS). Brushless motors allow a very fast strapping operation, granting also low maintenance, and improved electronic control. Equipped with high efficiency and long life Li-Ions battery, it can reach even more than 400 cycles per charge, without any memory effect.

TA 260 can be used in any application field, from timber to logistic, from steel to brick industry and, with the new „Soft Tensioning Mode“, also corrugated and all other light applications will not be a problem anymore.

Technical Data

| | |
|----------------------------|----------------------------|
| Kind of drive (tensioning) | Electric |
| Tension force | 500 – 2.500 N (adjustable) |

| | |
|-------------------------|--------------------------------|
| Kind of drive (sealing) | Electric |
| Power supply system | Li-Ion 18 V - 5 Ah |
| Strap feeding speed | 11 m/min. |
| Dimensions | 325 x 135 x 135 mm (L x B x H) |
| Weight | 4,4 kg |

Strap/Joint

| | |
|---|--|
| Type of strap | Plastic strap |
| Strap | PP PET |
| Strap width | 13, 16 mm |
| Strap thickness | 0,50 - 1,05 mm |
| Kind of seal | Friction-weld joint |
| Sealing strength (depending on strap quality, strap dimensions) | Approx. 75% of the strap breaking load |

Application

| |
|--|
| Strapping of flat packages (e.g. palletized goods) for mobile use. |
|--|