

Contact

Jutta Geurtz +49 2336 808295 jgeurtz@titan-schwelm.de



Battery powered strapping tool for plastic strap

The ultimate battery powerhouse

The TA 750 is the absolute top-of-the-range model in the TA family - with performance values that are second to none in the battery-powered hand-held segment: Thanks to the proven rechargeable battery of 36 Volt, it delivers a tensioning force of up to 7,000 N.

Strap widths in the range between 19 and 32 mm are thus routine. This kind of power development obviously requires maximum control. No problem for the TA 750! Other advantages reserved for users of TITAN hand-held tools are the excellent handling properties of the TA series, the extremely simple and intuitive operation using two buttons and, finally, the low weight.

Strapping in the steel and sheet metal sectors as well as of coils can be done with the TA 750 in no time at all

The power is in your fingertips.

Technical Data

Kind of drive (tensioning)	Electric
Tension force	2,700 - 8,000 N (adjustable)
Kind of drive (sealing)	Electric
Power supply system	36 V / 2.0 Ah / 72 Wh
Strap feeding speed	12 m/min. 39.4 ft/min.
Dimensions	300 x 150 x 200 mm (L x W x H) 11.8 x 5.9 x 7.9" (L x W x H)

Copyright TITAN Umreifungstechnik, GmbH & Co. KG | Berliner Straße 51-55 | 58332 Schwelm | Deutschland Contakt: Jutta Geurtz | +49 2336 808295 | jgeurtz@titan-schwelm.de

Weight	6.4 kg 14.1 lb
Handarm vibration	2.2 m/s ²
Noise level	81 dB (A)

Strap/Joint

Type of strap	Plastic strap
Strap	PP PET
Strap width	19 mm 3/4" 25, 32 mm 1" ; 1 1/4"
Strap thickness	0,80 - 1,40 mm 0.031 - 0.055" 1,00 - 1,30 mm 0.039 - 0.051"
Kind of seal	Friction-weld joint
Sealing strength (depending on strap quality, strap dimensions)	approx. 75% of the strap breaking load

Application

Strapping of flat packages (e.g. palletized goods) for mobile use.