

## **TA 260** 13-16 mm





## **FEATURES**

- Opening lever free
- Bluetooth connection & mobile APP
- Digital control Panel
- Very fast in tensioning and welding
- Automatic / Semi Automatic / Manual Soft Tensioning Mode
- Easy change of strap width

### **BENEFITS**

- Wide range & adjustable tension
- · Lightweight and well balanced
- Friction weld and high seal efficiency
- Easy access to wearing parts
- Strong and well protected motor housing

# The new TA 260 is a innovative and revolutionary battery strapping tool, developed for 13 – 16 mm PP and PET strap.

Lightweight, well balanced, ergonomic and easy to use.

The TA 260 can work in three different operating modes (fully automatic, semi-automatic and manual).

Developed without the standard opening lever for a more comfortable strapping operation. With the integrated Bluetooth connection you can set, check and update your tool. You can also use your mobile devices (APP available for Android and iOS). Brushless motors allow a very fast strapping operation, granting also low maintenance, and improved electronic control. Equipped with high efficiency and long life Li-lons battery, it can reach even more than 400 cycles per charge, without any memory effect.

TA 260 can be used in any application field, from timber to logistic, from steel to brick industry and, with the new "Soft Tensioning Mode", also corrugated and all other light applications will not be a problem anymore.

## BATTERY POWERED PLASTIC STRAPPING TOOL **TA 260**











#### **CONTACT**

**Anke Freitag** +49 2336 808295 afreitag@titan-schwelm.de

## **Technical Data**

Kind of drive (tensioning + sealing)	Electric
Tension force	500 – 2.500 N (adjustable)
Power supply system	Li-lon 18 V - 4 Ah
Strap feeding speed	11 m/min.
Dimensions	325 x 135 x 135 mm (L x B x H)
Weight	4.4 kg
Strap/Joint	
Type of strap	Plastic strap
Strap	PP / PET
Strap width	13, 16 mm
Strap thickness	0.50 – 1.05 mm
Kind of seal	friction weld
Sealing strength	Approx. 75% of the strap breaking load (depending on the belt quality, belt dimension)
Application	Strapping of flat packages (e.g. palletized goods) for mobile use



#### **TRADITION VERBINDET** · SEIT 1842

Unternehmen der Lenzen Gruppe / Companies of Lenzen Group:









## **Lenzen Gruppe**

Berliner Straße 51-55
58332 Schwelm
+49 2336 808 111
sekretariat@lenzen-Gruppe.de